

Dimensions

	Dimension (mm)						Capacity (Liter)	Applicable			
	External			Internal				NS	S	SS	US
	(W)idth	(D)epth	(H)eight	(W)idth	(D)epth	(H)eight					
DRY-60	400	442	556	398	385	480	71				
DRY-70	400	442	652	398	385	576	88				
DRY-100	400	442	882	398	385	808	124				
DRY-120L	806	430	480	804	375	405	122				
DRY-125	440	442	976	438	385	898	151				
DRY-190L	806	480	656	804	420	575	194				
DRY-205	400	530	1292	398	475	1210	228				
DRY-230	600	480	978	598	425	896	228				
DRY-300(M)	890	480	978	888	425	896	339				
DRY-420(M)	1200	480	1076	1198	425	896	456				
DRY-500(M)	890	860	1025	888	805	896	568				
DRY-520(M)	1200	570	1076	1198	515	896	552				
DRY-610	1400	600	1076	1398	545	896	682				
DRY-530 2 doors	890	660	1280	888	610	1130	612				
DRY-530 4 doors	940	660	1280	888	610	1130	612				
DRY-460	600	750	1390	598	695	1190	494				
DRY-700	600	750	2000	598	695	1810	754				
DRY-1360	1200	750	2010	1198	695	1810	1511				
DRY-1460	1200	750	1992	1198	695	1820	1527				
DRY-160H2	460	685	780	383	540	275	202				
DRY-240H3	460	685	1085	383	540	275	295				
DRY-320H4	460	685	1485	383	540	275	390				
DRY-150V3	460	685	720	388	540	150	184				
DRY-200V4	460	685	920	388	540	150	244				
DRY-250V5	460	660	1110	388	540	150	303				
DRY-500V5	890	660	1190	818	540	150	588				
DRY-500V10	890	660	1190	360	540	150	588				
DRY-720V5	1000	750	1190	928	640	150	732				
DRY-310GW	912	538	915	865	440	790	313				
DRY-310W	912	538	915	860	440	830	313				